

# SPECTRUM SCOREBOARDS

## Product Specifications for Model [10308-C2](#) Softball or Baseball Scoreboard

MAY 2011

### PART 1 GENERAL

#### 1.01 SECTION INCLUDES:

- A. Exterior single-sided LED softball and baseball scoreboard with control center.

#### 1.02 REFERENCES

- A. Standard for Electric Signs, UL-48
- B. Standard for Control Centers for Changing Message Type Signs, UL-1433, 1<sup>st</sup> Edition
- C. Federal Communications Commission Regulation Part 15
- D. National Electric Code

#### 1.03 SUBMITTALS

- A. Product Details: Submit literature for manufacturer scoreboard, control and accessories as specified.
- B. Specification Drawings: Submit face layout, dimensions, electrical wiring diagrams, structural support and mounting.
- C. Resources: Submit manufacturer installation instructions and operation manual.

#### 1.04 PROVISIONS

**\*\* NOTE TO SPECIFIER \*\*** Following conditions shall be reviewed with customer

- A. Shall verify mounting structure is secured and cured.
- B. Shall verify location of scoreboard equipment and structure is prepared for installation, as specified.
- C. Shall verify mounting structure is able to support the scoreboard and accessories weight and wind load. Mounting structure is the responsibility of the Architect, unless otherwise specified.
- D. Shall confirm conduit locations, number of conduit run and termination of conduit.

#### 1.05 QUALITY ASSURANCE

- A. Source Limitations: Provide scoreboard and components through one source from a single manufacturer.
- B. Scoreboard designed for outdoor use.
- C. Shall be ETL listed for UL Standards 48 and 1433
- D. Shall be FCC compliant
- E. Shall be NEC compliant

## **1.06 WARRANTY AND SERVICE PLAN**

- A. Spectrum Solid State Scoreboards are guaranteed for a period of five (5) years against any defects in materials.
- B. Warranty does not cover unauthorized repairs or modifications, abuse, neglect, acts of God, exceptionally high or low voltage, and/or improper grounding, installation, operation or shipment to the factory.

## **PART 2 PRODUCT:**

### **2.01 MANUFACTURER**

- A. Spectrum Corporation, 10048 Easthaven Blvd., Houston, TX 77075  
Phone: 713-944-6200, 800-392-5050, Fax: 713-944-1290  
Website: [spectrumscoreboards.com](http://spectrumscoreboards.com)

### **2.02 PRODUCT OVERVIEW**

- A. Scoreboard Model 10308-C2 with MS-250 scoring console for softball and baseball.  
Scoreboard shall have the following displays:
  - 1:59 MINUTE CLOCK/TIMER
  - HOME and VISITOR score
  - INNING
  - BALL, STRIKE, and OUT INDICATORS
  - TEAM NAME IN PLACE OF HOME (OPTIONAL)

## 2.03 SCOREBOARD

### A. General Information

1. Dimensions: 6 feet high x 8 feet wide x 5 inches deep  
(1.8 m x 2.4 m x 13 cm)
2. Weight: 151 lbs. (70 kg)
3. Power requirements: 275 VA, 120 Vac, 60 Hz
4. Shall have a Premium Polyurethane Finish
5. Select from stock colors or match to a PMS color (number \_\_\_\_\_)
6. Shall have Border Trim and Clock Striping
7. Scoreboards functionality shall include:
  - 1:59 MINUTE CLOCK/TIMER
  - Segment Timer capable (with MSX)
  - Home & Visitor score 0-99 with programmable Celebration “Flash” feature
  - Inning, 0-9
  - Bullseye indicators for Ball, Strike and Out
  - Instant reset and posting for all digits

### B. Construction

1. Scoreboard face: .063 Aluminum with premium polyurethane finish
2. Scoreboard back: .050 mill finish aluminum
3. Digit face plate: .063 thick

### C. Digits

1. Shall be constructed of AlInGaP Light Emitting Diodes (LEDs)
2. Shall be a combination of red and amber LED digits
3. Shall be rated 100,000 hours of use
4. Shall be 8-segment solid stroke design
5. All pixels shall be interchangeable throughout the scoreboard
6. All pixels shall be conformal coated front and back to protect the electronics from environmental conditions
7. All pixels shall be individually gasketed for weather protection
8. All pixels shall be individually serviceable from the front of the scoreboard cabinet
9. Scoreboard assembly shall include eight (8) numeric LED digits and seven (7) indicators
10. Digit sets shall have:
  - SpectraBrite LED digit technology  
18” (46 cm) high – Home and Visitors scores.  
Shall include 80 LEDs per digit
  - 15” (38 cm) high – Clock and Innings  
Shall include 52 LEDs per digit

### D. Captions

1. HOME, VISITOR, INNING, BALL, STRIKE and OUT shall be 8” high (20 cm)
2. Captions shall be 3M brand 220 High Performance Vinyl applied directly to scoreboard face

## 2.04 CONTROL SCORING CONSOLE

1. Control shall be a MS-250 controller.
2. Controller functionality shall include:
  - Easy set up for different sports.
  - Memory backup to retain configurations and eliminate data loss
  - Durable, lockable rugged waterproof carry case
  - A ten (10) foot (3 m) low voltage data cable cord that connects to control receptacle junction box and shall unplug and store inside the carrying case
  - Does NOT require hazardous 120 VAC electrical power
3. Easy Programming:
  - Celebrate a home score with flashing numbers
  - Option to use as a Practice Segment Timer or Time of Day Clock (with MSX Controller upgrade)
4. Connection Options:
  - Direct wire, powered through control cable
  - Radio
  - Battery operation with radio - fully autonomous

## 2.05 AVAILABLE SCOREBOARD OPTIONS

**\*\* NOTE TO SPECIFIER \*\*** *Select scoreboard options*

1. Team Name caption in place of HOME caption
2. Digit Style: Pro-Style, Ultra-Bold, SpectraBrite™
3. Digit Color: All Red, All Amber, Combination Red and Amber
4. Color Options: Add a custom two-tone color to the scoreboard
5. Finish: Perma-Coat adds protection to finish and vinyl
6. Border Trim Striping Style: Curve, Oval, Octagon, Square
7. Clock Striping Style: Curve, Oval, Octagon, Square
8. Lettering: Standard, Outlined, Shadow
9. Mascot: Standard to extra-large size in 1-color, 2-colors, 3-colors, or full-color
10. Caption Option: Backlit Captions
11. Additional scoreboard functions per purchase order

## **2.06 AVAILABLE UPGRADES AND ACCESSORIES**

1. Multi-Sport Captions Plates
2. Controller Clock Handswitch for second operator
3. Radio Controller
4. Electronic Team Names
5. Electronic Message / Animations Displays
6. Video Display (custom designed to fit scoreboard)
7. School and/or Sponsor Signs
8. Scoreboard Accents (truss, arches, lettering, pole wraps, flags)
9. Clocks and Timers

## **PART 2 EXECUTION**

### **3.01 EXAMINATION**

#### **A. Verification**

1. Confirm the mounting structure is completely cured and prepared for scoreboard. Verify plans and specification drawings are in accordance with manufacture's instructions and approved drawings.

#### **B. Installation**

1. Confirm scoreboard location. Verify electrical requirements have proper power source.
2. Confirm conduit and wiring are in place to be routed to scoreboard and accessories as shown on electrical plans by the Electrical Contractor. The contractor assigned the scoreboard equipment shall be responsible for all routing of conduit and wiring.
3. Secure scoreboard and confirm accessories are level and plumb with brackets and fasteners.
4. Test scoreboards and accessories to ensure all operations performing accurately.
5. Clean and touch-up any exposed areas.

Specifications are subject to change without notice.

Copyright © Spectrum Corporation 2011. All rights reserved. Spectrum, the Spectrum logo, Spectrum Scoreboards, SpectraBrite, SpectraLite and SpectraShield are trademarks of Spectrum Corporation.

END OF SECTION